

Maipu MPS4108G-G4 Series GPU Server Datasheet

Overview

Maipu MPS4108G-G4 is a 4U 8*GPU AI Server developed by Maipu, based on Intel's latest Eagle Stream platform, offering powerful computing capabilities and highly flexible expansion options. It supports direct CPU-GPU connections and CPU-GPU switch topologies, meeting the application needs of various AI scenarios. It is suitable for applications in artificial intelligence, cloud computing, virtualization, big data analysis, and digital twins.



Key Features

- Supports 1 or 2 Intel® Xeon® Scalable Processors (4th/5th generation) with a maximum TDP of 350W □
- Upto 32 DDR5 memory slots, supporting memory frequencies of 4400/4800/5600MHz, with a 75% increase in memory bandwidth □
- Onboard 2 M.2 SATA/NVMe interfaces □
- Supports direct CPU-GPU connection and CPU-GPU switch expansion mode, supports 600W dual-width GPU cards □
- Supports SATA/SAS/NVMe tri-mode hard drive configurations, meeting high-speed transmission and data storage needs

Technical Specifications

Product Model	MPS4108GD12R-G4	MPS4108GD24R-G4
Form Factor	Pass-though 8-GPU 12-Bay AI Server	Switch 8-GPU 24-Bay AI Serve
System Size	850*444*176.5mm (Depth*Width*Height)	
Processor	Supports 1 or 2 4th/5th generation Intel® Xeon® Scalable processors, with a maximum TDP of 350W	
Memory	32*DDR5 memory slots, supporting DDR5 RDIMM 4400/4800/5600MHz memory	
Internal Storage Interface	2*Slimline4xinterfaces(SATA),2*M.2slots(2280/22110,SATA/PCIe3.0x1)	
External Hard Drive	Support 12*hot-swappable 3.5/2.5-inch SAS/SATA/U.2 hard drives	Support 24*hot-swappable 2.5-inch SAS/SATA/U.2 hard drives
External Ports & Buttons	Front: 1*VGA, 2*USB3.0, Rear: 1*VGA, 1*RJ45 Gigabit Ethernet ports, 1*Serial port, 2*USB3.0	
PCIe Expansion	Up to 13*PCIe expansion slots(OCP3.0 card can be optionally configured as PCIe5.0 x8 or x16,which is mutually exclusive with one of the PCIe5.0 standard single-width slots)	Upto15*PCIe5.0 expansion slots + 1*OCP3.0slot
Security	Support TPM Module (Optional)	
Power Supply	3+1 or 2+2 Redundancy (2000W/2200W/2600W/3200W)	
FAN	Standard 12*hot-swappable 6056 N+1 redundant fans	
IPMI	IPMI 2.0	
Management	1*DC0 RJ45 Management Port	
Temperature	Working Temperature 5°C–35°C Short-term storage (≤72 hours): -40°C ~ 70°C Long-term storage (>72 hours): 20°C ~ 28°C	
Humidity	Working Humidity 20%–80%RH non-condensing Short-term storage (≤72 hours): 20% ~ 90% RH (non-condensing, including packaging) Long-term storage (>72 hours): 30% ~ 70% RH (non-condensing, including packaging)	

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd

No.16, Jiuxing avenue

Hi-Tech Zone

Chengdu, Sichuan Province

P. R. China

610041

Tel: (86) 28-65544850,

Fax: (86) 28-65544948,

URL: [http:// www.maipu.com](http://www.maipu.com)

Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.