

Maipu MPS201S-G3 Series Rack Server Datasheet

Overview

Maipu MPS201S-G3 is a standard 2U dual-socket server, supporting 1 or 2 3rd generation Intel® Xeon® Scalable processors, 16*DIMM DDR4 memory slots, supports 1*M.2 interfaces, 2*RJ45 Ethernet ports, 1*RJ45 management port, and 10*PCIe expansion slots. It is suitable for virtualization, cloud computing, big data processing, high-performance computing, distributed storage, enterprise markets, or telecommunications business applications, and more.



Key Features

- Supports 1 or 2 3rd generation Intel® Xeon® Scalable processors, with a maximum TDP of 205W
- Supports a maximum of 16*DDR4 memory slots, with memory frequencies of 2666/2933/3200MHz
- 1* built-in NVMe PCIe 3.0 M.2 interfaces
- Up to 10*PCIe high-speed expansion slots, providing rich expansion performance
- 10*half-height high-performance GPUs or 2*full-height, double-width high-performance GPUs to meet the needs of high computing power

Technical Specifications

Product Model	MPS201SD08R-G3	MPS201SD12RE-G3
Form Factor	2U 8*SATA/SAS Direct-Connect Server	2U 12*SATA/SAS Expansion Server
External Hard Drive	Front: support 8*hot-swappable 3.5/2.5-inch SAS/SATA/U.2 hard drives Rear: optional support 2×2.5-inch SAS/SATA/U.2 hard drive modules	Front: support 12*hot-swappable 3.5/2.5-inch SAS/SATA/U.2 hard drives Rear: optional support 2×2.5-inch SAS/SATA/U.2 hard drive modules
System Size	695*433*87.6mm (Depth*Width*Height)	
Processor	Supports 1 or 2 3rd generation Intel® Xeon® Scalable processors	
Memory	16*DDR4 memory slots, supporting DDR4 LRDIMM/RDIMM 2666/2933/3200MHz memory	
Internal Storage Interface	3*Mini SAS HD interfaces, 2*SATA DOM interfaces, 1*NVMe PCIe 3.0*4 interfaces	
External Ports & Buttons	Front: 2*USB 3.0, 1*Power button, 1*Reset button, 1*Hard disk indicator, 1*System fault indicator, 2*Network status indicators Rear: 1*VGA, 2*RJ45 Gigabit Ethernet ports, 1*RJ45 Gigabit Management port, 1*COM port, 2*USB3.0	
PCIe Expansion	<p>10*PCIe half-height version: Support 6*half-height PCIe 3.0x8 (in PCIe 3.0 x16 slot), 1*half-height PCIe 3.0x16 and 3*half-height PCIe 4.0x16; Optional support for 4*half-height PCIe 3.0x8 (in PCIe 3.0 x16 slot), 2*half-height PCIe 3.0x16, and 3*half-height PCIe 4.0x16</p> <p>7*PCIe half-height version: Support 4*half-height PCIe 3.0x8 (in PCIe 3.0 x16 slot) and 3*half-height PCIe 4.0x16; Optional support for 2*half-height PCIe 3.0x8 (in PCIe 3.0 x16 slot), 1*half-height PCIe 3.0x16, and 3*half-height PCIe 4.0x16</p> <p>1*PCIe full-height, double-width version: Support 1*full-height, double-width PCIe3.0 x16, 6*half-height PCIe 3.0x8 (in PCIe x16 slot), 1*half-height PCIe 3.0x16 and 2*half-height PCIe 4.0x16</p> <p>2*PCIe full-height, double-width version: Support 1*full-height, double-width PCIe4.0 x16, 1*full-height, double-width PCIe3.0 x16 and 3*half-height PCIe x8</p>	
Security	Support TPM Module (Optional)	
Power Supply	Optional AC 220V 550W、800W、1300W、1600W 1+1 redundant power supply(adapted to actual power requirements)	
FAN	Standard 4 hot-swappable N+1 redundant fans, supporting 8038/8056 specifications (7PCIe version: 3* 8038/8056 hot-swap fans)	
IPMI	IPMI 2.0	
Management	1*DC0 RJ45 Management Port	
Temperature	Working Temperature 5°C–35°C Short-term storage (≤72 hours): -40°C ~ 70°C Long-term storage (>72 hours): 20°C ~ 28°C	
Humidity	Working Humidity 20%–80%RH non-condensing Short-term storage (≤72 hours): 20% ~ 90% RH (non-condensing, including packaging) Long-term storage (>72 hours): 30% ~ 70% RH (non-condensing, including packaging)	

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd
No.16, Jiuxing avenue
Hi-Tech Zone
Chengdu, Sichuan Province
P. R. China
610041
Tel: (86) 28-65544850,
Fax: (86) 28-65544948,
URL: [http:// www.maipu.com](http://www.maipu.com)
Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.



FACEBOOK



LINKEDIN