

S4330 Series Stackable L3 Aggregation Switch





Datasheet



Overview

The S4330 series switch is a high-performance stackable L3 aggregation routing switch developed by Maipu. It is applied in enterprise campus network and easy to deploy Layer3 switching solution that offers enhanced security and 10GE uplinks, RIP/OSPF/BGP/IS-IS, L2&L3 Multicast, VST/M-LAG stacking enabled and flexible management like SDN management and Cloud managed.

The S4330 series switch can be used as L3 access devices on large-sized campus networks. They can also be used as aggregation devices on small and medium-sized campus networks. The switches help build highly reliable enterprise campus networks that are easy to expand and manage.

The S4330 series switch includes S4330-30TXF, S4330-30TXP, S4330-54TXF, S4330-54TXP, S4330-54GXF, S4330-54TGXF models.

| Model Name | Specification |
|---|--|
|  <p>S4330-30TXF</p> | <ul style="list-style-type: none"> ● 24*10/100/1000M Base-T + 4*10G SFP+ ● One Extension Slot (2-Port 10G Card) ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● Switching Capacity: 168Gbps |
|  <p>S4330-54TXF</p> | <ul style="list-style-type: none"> ● 48*10/100/1000M Base-T + 4*10G SFP+ ● One Extension Slot (2-Port 10G Card) ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● Switching Capacity: 216Gbps |
|  <p>S4330-30TXP</p> | <ul style="list-style-type: none"> ● 24*10/100/1000M Base-T + 4*10G SFP+ ● One Extension Slot (2-Port 10G Card) ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● 380W/760W PoE&PoE+ ● Switching Capacity: 168Gbps |
|  <p>S4330-54TXP</p> | <ul style="list-style-type: none"> ● 48*10/100/1000M Base-T + 4*10G SFP+ ● One Extension Slot (2-Port 10G Card) ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● 380W/760W/1440W PoE&PoE+ ● Switching Capacity: 216Gbps |

| | |
|--|---|
|  <p>S4330-54GXF</p> | <ul style="list-style-type: none"> ● 48*1G SFP + 4*10G SFP+ ● One Extension Slot (2-Port 10G Card) ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● Switching Capacity: 216Gbps |
|  <p>S4330-54TGXF</p> | <ul style="list-style-type: none"> ● 32*10/100/1000M Base-T + 16*1G SFP ● 4*10G SFP+ ● Dual Modular Power Slots ● RJ45 Console/USB2.0 Port ● Switching Capacity: 216Gbps |

Key Features

● Intelligent stacking technology

The S4330 series switch is equipped with Maipu VST stacking function that allows a minimum of four devices to be stacked into one logical device via the 10G SFP+ ports. VST (Virtual Switching Technology) stacking combines multiple switches to form a logical virtual switch, improving device and link reliability, network expansion, and simplifying configuration and management.

● Software Defined Network

The S4330 series switch is capable of being managed by Maipu's BD-Campus controller, an integrated SDN platform designed for campus networks. The utilization of software-defined network technologies in this platform simplifies the deployment, management, and security of campus networks, while also enabling network teams to complete the majority of their work directly on the BD-Campus controller platform. When compared with traditional methods, implementing a BD-Campus solution can significantly reduce network deployment times, simplify network maintenance, improve troubleshooting efficiency, and ultimately lead to overall cost savings for customers.

● Zero Touch Provisioning

The S4330 series switch features advanced Zero Touch Provisioning (ZTP) capabilities, streamlining the deployment process for network administrators. With ZTP, the switch can automatically discover and load necessary version files from a file server via a DHCP server or a USB flash disk, eliminating the need for manual intervention during initial setup. This automation reduces configuration errors, accelerates the deployment process, and enhances overall network efficiency, making the S4330 series switch an ideal choice for scalable and dynamic network environments.

● High availability

The S4330 series switch offers advanced redundancy and reliability features, catering to diverse networking requirements. In addition to supporting traditional spanning tree protocols such as STP, RSTP, and MSTP, the switch also complies with the ITU-T G.8032 international standard. This Ethernet Ring Protection Switching (ERPS) protocol enables rapid 50ms failover within Ethernet ring network topologies, ensuring seamless connectivity and minimal downtime.

Furthermore, the S4330 series switch incorporates the Virtual Router Redundancy Protocol (VRRP), facilitating uplink backup capabilities. By connecting to multiple aggregation switches via multiple links, the switch significantly enhances access device reliability, promoting network stability and resilience.

● Perfect security policy

The S4330 series switch offers a comprehensive suite of security features, including user authentication, port security, ACLs, loopback detection, and 802.1X authentication. It also incorporates IP Source Guard, DHCP/ND Snooping, Host Guard, Dynamic ARP Inspection, and PPPoE+ security mechanisms. These robust security functions ensure user access and network protection.

Additionally, the switch supports MAC+IP+VLAN binding, 802.1X authentication, and countermeasures against network storm, DOS/DDOS, ARP, and protocol packet attacks. This makes the S4330 series ideal for large-scale, multi-service, and complex-traffic networks.

● Advanced QoS

The S4330 series switch offers sophisticated QoS capabilities for optimal network performance. Supporting eight queues per port and advanced scheduling algorithms such as SP, RR, WRR, and WDRR, the switch effectively manages traffic prioritization and resource allocation.

The switch accommodates diverse priority mapping techniques, including 802.1p, CoS, and DSCP, enabling fine-grained control over traffic classification and prioritization. With granular port traffic rate limiting and time-based controls, network administrators can regulate bandwidth usage as needed.

To optimize network performance and minimize congestion, the S4330 series switch employs advanced congestion management techniques, such as Tail Drop and RED packet loss algorithms. These mechanisms help maintain seamless network operation while ensuring efficient delivery of critical data.

● **IPv4&IPv6 Dual-stack ability**

The S4330 series switch is built on an IPv4/IPv6 dual-stack platform, delivering hardware-based, wire-speed forwarding for both IPv4 and IPv6 traffic. The switch supports IPv4/IPv6 Layer 3 routing protocols, including RIPng, OSPFv3, BGP4+, and IS-IS for IPv6. These IPv6 capabilities enable seamless deployment on pure IPv4, pure IPv6, or dual-stack networks, facilitating a smooth transition from IPv4 to IPv6 infrastructure.

● **Rich Network Management**

The S4330 series switch offers a comprehensive set of management options. These options encompass network management protocols like SNMP and TR-069, configuration and control options like Netconf/Yang and CLI, monitoring and diagnostic tools such as RMON and SYSLOG. These versatile features enable network administrators to effectively manage, monitor, and maintain optimal network performance both locally and via the cloud.

● **Free Licensing Policy**

Maipu consistently adheres to a "One-time investment" free license policy, ensuring that standard and advanced features are not differentiated across versions. This approach guarantees that customers receive new firmware updates without incurring additional charges. In comparison to other manufacturers, Maipu's free license policy safeguards both short-term and long-term user investments, providing an unparalleled value proposition.

Technical Specifications

| Model | S4330-30TXF | S4330-30TXP | S4330-54TXF | S4330-54TXP | S4330-54GXF | S4330-54TGXF |
|---------------------------------|--|--|--|--|---|--|
| Hardware Specification | | | | | | |
| Physical Traffic Port | 24*10/100/1000M Base-T interfaces 4*10G SFP+ interfaces | 24*10/100/1000M Base-T interfaces 4*10G SFP+ interfaces | 48*10/100/1000M Base-T interfaces 4*10G SFP+ interfaces | 48*10/100/1000M Base-T interfaces 4*10G SFP+ interfaces | 48*1G SFP interfaces 4*10G SFP+ interfaces | 32*10/100/1000M Base-T interfaces 16*1G SFP interfaces 4*10G SFP+ interfaces |
| Extension Slot | One | One | One | One | One | One |
| Power Slot | Dual | Dual | Dual | Dual | Dual | Dual |
| Fixed Fan | Yes | Yes | Yes | Yes | Yes | Yes |
| PoE Power Consumption | N/A | 380W/760W | N/A | 380W/760W/1440W | N/A | N/A |
| PoE Standard | N/A | IEEE 802.af/at | N/A | IEEE 802.af/at | N/A | N/A |
| Power Consumption (Without PoE) | ≤34W | ≤34W | ≤46W | ≤46W | ≤76W | ≤49W |
| Dimension(W*D*H)mm | 442*420*44.2 | 442*420*44.2 | 442*420*44.2 | 442*420*44.2 | 442*420*44.2 | 442*420*44.2 |
| Physical Management Port | 1*RJ45 Console 1*USB2.0 Port | | | | | |
| Input Voltage | AC:100—240V/50-60Hz DC: 40~57V | | | | | |
| Temperature | Work Temperature: -5℃ to 50℃ Storage Temperature: -40℃ to 70℃ | | | | | |
| Humidity | Work Humidity:10% ~ 90%, non-condensing Storage Humidity:5% ~ 95%, non-condensing | | | | | |
| Anti-Lightning | 6KV | | | | | |
| Anti-Static | 6KV | | | | | |
| MTBF | >100000 hours | | | | | |
| Performance Parameters | | | | | | |
| Switching Capability | 168Gbps | 168Gbps | 216Gbps | 216Gbps | 216Gbps | 216Gbps |
| MAC Address Entry | 32K | 32K | 32K | 32K | 32K | 32K |
| Jumbo Frame | 12K | 12K | 12K | 12K | 12K | 12K |
| ARP Entry | 8K | 8K | 8K | 8K | 8K | 8K |
| ND Entry | 8K | 8K | 8K | 8K | 8K | 8K |
| VLAN Entry | 4K | 4K | 4K | 4K | 4K | 4K |
| LACP Group | 64 | 64 | 64 | 64 | 64 | 64 |
| LACP Member in Group | 8 | 8 | 8 | 8 | 8 | 8 |
| MSTP Instance | 64 | 64 | 64 | 64 | 64 | 64 |
| IPv4 Routing Entry | 12K | 12K | 12K | 12K | 12K | 12K |

| | | | | | | |
|--------------------|-----|-----|-----|-----|-----|-----|
| IPv6 Routing Entry | 4K | 4K | 4K | 4K | 4K | 4K |
| L2 Multicast Entry | 6K | 6K | 6K | 6K | 6K | 6K |
| L3 Multicast Entry | 6K | 6K | 6K | 6K | 6K | 6K |
| VRF Entry | 256 | 256 | 256 | 256 | 256 | 256 |
| VRRP Group | 255 | 255 | 255 | 255 | 255 | 255 |

Software Specification

| | | |
|---------------------|-----------------------------|--|
| Interface | Physical Interface | Auto MDI/MDIX , Port Type UNI/NNI, Port Speed, Port MTU, Switch Port, Port Loopback, Port Energy Control |
| | Logic Interface | Loopback Interface, Tunnel Interface, Null Interface |
| | MAC Address Management | Storm Control, Flood Control, MAC Address Aging Time, Mac Address Learning on/off, Mac Address Learning Limitation, Mac Address VLAN Bundling, MAC Debug |
| VLAN | VLAN Management | VLAN, QinQ, Flexible QinQ, VLAN PVID, VLAN Tag/Untag, VLAN Trunk, MAC VLAN, Protocol VLAN, Subnet VLAN, Super VLAN, Voice VLAN, Private VLAN, Guest VLAN, VLAN Debug, GVRP, VLAN Isolation |
| Ring Protection | Spanning Tree Protocols | STP/RSTP/MSTP, BPDU Guard, Flap Guard, Loop Guard, Root Guard, TC Guard |
| | Other Ring Protocols | VIST/VIST+, G.8032(ERPSv1&v2) |
| Link Aggregation | LACP Configuration | LACP Link Aggregation, LACP Port Priority, LACP Load Balance, LACP Rate Monitor, LACP Debug |
| Error Handling | Error-disable Configuration | Error-disable Based on bpduguard Dai DHCP Snooping Link-Flap Loopback-detect Port Security Storm Control Transceiver Power, Error-disable Recovery |
| Fault Detection | Fault Detection Features | ULFD, Track, Loop-back Detection, CFM(802.1ag) |
| IP Services | IP Protocol | ARP, DNS, NTP Server/Client, ICMP, ECMP, GRE, IPIP, IPv6 over IPv4, ISATAP, IPv4 over IPv6, IPv6 over IPv6 |
| | Routing Protocol | Static Routing v4/v6, RIP/RIPng, OSPF v2/v3, BGP/BGP+, ISIS/ISIS v6, VRRP/VRRP v3, VBRP, PBR/PBR v6, IP-VRF |
| | DHCP Service | DHCP v4/v6 Server, DHCP v4/v6 Client, DHCP v4/v6 Relay, DHCP Snooping, DHCP Option51/82 |
| Multicast Protocols | L2 Multicast Protocols | IGMPv1/v2/v3 Snooping, IGMP Snooping Proxy, MLD Snooping, MVR, MVP |
| | L3 Multicast Protocols | IGMPv1/v2/v3, PIM v4/v6-SM, PIM v4/v6-SSM, PIM-DM, PIM-SDM, |
| QoS | Priority Mapping | 802.1P Priority, DSCP priority |
| | Traffic Classification | Three Color Marker, Priority Remark, Traffic Redirect, Traffic Meter, Traffic Mirror |
| | Traffic Control | Rate Limit, Traffic Shaping |
| | Scheduling Algorithm | SP, RR, WRR, WDRR, SP+WRR, SP+WDRR |
| | Congestion Management | Tail-drop, RED, WRED |
| Security | Port Security | Port Security On aging deny permit violation ACL |
| | Network Access Control | IP Source Guard(ISG), DHCP Snooping, ND Snooping, Host Guard |
| | Threat Prevention | Dynamic ARP Inspection(DAI), ARP Check, AARF ARP-Guard, ARP Guard, PPPoE+ |
| | Access Control List | Standard IP ACL, Extended IP ACL, Standard MAC ACL, Extended MAC ACL, Standard Hybrid ACL, Extended Hybrid ACL, Standard IPv6 ACL, Extended IPv6 ACL, Time-based ACL |
| | Anti-Attack | Anti-Attack Detect Drop Flood Log, URPF, White List, Black List |


| | | |
|-------------------------------|--|---|
| | AAA | AAA, Radius, TACACS+, 802.1x, Portal |
| High Availability | Device Virtualization | H-VST, M-VST |
| | Multi-Active Detection | MAD LACP, MAD BFD, MAD Fast-Hello, MAD LACP |
| | High Availability Protocols | HA, ULFD, UDLD, G.8032, ULPP, Monitor Link, VRRP, VRRPv3, VBRP, EEP, BFD with Static RIP OSPF BGP ISIS, CPU protection |
| Configuration and Maintenance | Monitoring and Diagnostics | SPAN, RSPAN, VLAN SPAN, sFlow, Telemetry, LLDP, IP-SLA |
| | Device Management | TR069, SNMP v1/v2/v3, MIB, RMON, SYSLOG, WEB(HTTP/HTTPS), CLI, Telnet, FTP/SFTP/TFTP/FTPS, Debug, Telemetry, ISSU, Hot Patch, Keepalive Gateway, Cloud Management |
| | Zero Touch Provisioning | ZTP Provisioning Through DHCP Server, ZTP Provisioning Through USB Flash Disk |
| Network Virtualization | Software Defined Networking (SDN) | Netconf/Yang |
| IEEE Standard | IEEE 802.3 (10BASE-T) IEEE 802.3u (100BASE-T) IEEE 802.3z (1000BASE-X) IEEE 802.3ab (1000BASE-T) IEEE 802.3ae (10G BASE-X) IEEE 802.3ah (Ethernet in the First Mile Operations, Administration, and Maintenance) IEEE 802.1x (Port-Based Network Access Control) IEEE 802.3ad (Link Aggregation) IEEE 802.3x (Flow Control) IEEE 802.3az (Energy Efficient Ethernet) IEEE 802.1d (Spanning Tree Protocol) IEEE 802.1ab (Link Layer Discovery Protocol) IEEE 802.1Q (Virtual LAN) IEEE 802.1w (Rapid Spanning Tree Protocol) IEEE 802.1s (Multiple Spanning Tree Protocol) IEEE 802.1p (Class of Service Priority) IEEE 802.1ag (Connectivity Fault Management) | |

Order Information

| Model | Description |
|--------------------------|---|
| S4330 Series Host | |
| S4330-30TXF | 24*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots. |
| S4330-30TXP | 24*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots, PoE&PoE+ Enable. |
| S4330-54TXF | 48*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots. |
| S4330-54TXP | 48*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots, PoE&PoE+ Enable. |
| S4330-54GXF | 48*100/1000M SFP interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots. |
| S4330-54TGXF | 32*100/1000M Base-T interfaces, 16*100/1000M SFP interfaces, 4*10G SFP+ interfaces, One Extension Slot, Dual Power Slots. |
| Power Module | |
| AD120-1S005E | 120W AC Power Module (For Non-POE model) |
| AD500-1D005E | 500W AC Power Module (For POE model) |
| AD880-1D005E | 880W AC Power Supply Module (Only for S4330-54TXP) |
| DD250-5D005E | 120W DC Power Module (For Non-POE model) |
| Extension Module | |
| SM4C-2XGEF | 2-Port 10G SFP+ Extension Module |
| Stacking Cable | |
| SFP-STACK-15 | High speed stacking cable, SFP+ to SFP+,10Gbps, L=1.5m |
| SFP-STACK-30 | High speed stacking cable, SFP+ to SFP+,10Gbps, L=3.0m |
| SFP-STACK-50 | High speed stacking cable, SFP+ to SFP+,10Gbps, L=5.0m |

Typical Application

- SDN Campus Network



All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd
Maipu Mansion, No.16, Jiuxing Avenue
Hi-Tech Zone
Chengdu, Sichuan Province
P. R. China
610041
Tel: (86) 28-65544850,
Fax: (86) 28-65544948,
URL: [http:// www.maipu.com](http://www.maipu.com)
Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.



FACEBOOK



LINKEDIN