

MAIPU		MAIPU PARTNER PRICE LIST	
ID	Model	Description	Unit Price/USD
1	NSS5950-32QFP	Maipu NSS5950-32QFP ; 32*100G QSFP28 fiber port, modüler yedekli güç kaynağı, VERİ MERKEZİ ANAHTARLAMA CİHAZI,	15,625
2	NSS5830-56XQFP	Maipu NSS5830-56XQFP ; 48*10G SFP+ fiber port, 8*100G QSFP28 fiber port, modüler yedekli güç kaynağı, VERİ MERKEZİ ANAHTARLAMA CİHAZI	8,750
3	NSS5830-32XQFP	Maipu NSS5830-32XQFP ; 24*10G SFP+ fiber port, 8*100G QSFP28 fiber port, modüler yedekli güç kaynağı, VERİ MERKEZİ ANAHTARLAMA CİHAZI	8,125
4	NSS5810-26XF	Maipu NSS5810-26XF ; Full Layer 3 24*10G SFP+ fiber port, 2*40G QSFP fiber port, yedekli-modüler güç ve fan slotu, ANAHTARLAMA CİHAZI	3,000
5	NSS4330-60GXF	MAIPU NSS4330-60GXF ; Full Layer 3 48*1G SFP port, 4*10G SFP+ fiber port, yedekli güç kaynağı slotu, 2 adet genişleme yuvası, ANAHTARLAMA CİHAZI	2,188
6	S4230-36GTXF-AC	MAIPU S4230-36GTXF-AC ; 24 adet 1000M SFP fiber port, 8 adet 10/100/1000M RJ45 bakır port, 4 adet 10G SFP+ fiber arayüz, çift yedekli AC güç kaynağı, ANAHTARLAMA CİHAZI	813
7	S3330-28GXF-AC	Maipu S3330-28GXF-AC ; Layer 3 Lite 24* 1G SFP fiber port, 4*10G SFP+ fiber port, yedekli AC güç kaynağı, ANAHTARLAMA CİHAZI	788
8	S3230-28TXP-AC	Maipu S3230-28TXP-AC ; 24*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, POE/POE+ 380W, AC sabit güç kaynağı, ANAHTARLAMA CİHAZI	788
9	S3230-54TXP-AC	Maipu S3230-54TXP-AC ; 48*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, POE/POE+ 760W, AC sabit güç kaynağı, ANAHTARLAMA CİHAZI	1,438
10	S3330-28TXP-AC	Maipu S3330-28TXP-AC ; Layer 3 Lite 24*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, yedekli AC güç kaynağı, POE/POE+ 380W, ANAHTARLAMA CİHAZI	1,125
11	S3330-54TXP-AC	Maipu S3330-54TXP-AC ; Layer 3 Lite 48*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, yedekli AC güç kaynağı, POE/POE+ 380W, ANAHTARLAMA CİHAZI	1,813
12	IS230-28TP-AC	Maipu IS230-28TP-AC ; SMB Layer 2 24*10/100/1000M RJ45 port, 4*1G SFP fiber port, 380W POE/POE+ sabit AC güç kaynağı, ANAHTARLAMA CİHAZI	438
13	IS230-54TXP-AC	Maipu IS230-54TXP-AC ; SMB Layer 2 48*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, 380W POE/POE+, sabit AC güç kaynağı, ANAHTARLAMA CİHAZ	1,032
14	MP-S85123-3CDLM	Maipu MP-S85123-3CDLM ; 1.25G SFP 850nm 550m LC DDM Multi-mode	150
15	MP-S31121-3CDL20	Maipu MP-S31121-3CDL20 ; 1.25G SFP 1310nm 10-20Km LC DDM Single-mode	157
16	MP-S851X3-NCLM	Maipu MP-S851X3-NCLM ; 10G SFP+ 850nm 300m LC DDM Multi-mode	313
17	MP-S311X2-NCL10	Maipu MP-S311X2-NCL10 ; 10G SFP+ 1310nm 10Km LC DDM Single-mode	388
18	MP-QSFP-SR4	Maipu MP-QSFP-SR4 ; 40G QSFP+ 100m MPO DDM Multi-mode	375
19	MP-QSFP-LR4	Maipu MP-QSFP-LR4 ; 40G QSFP+ 10km LC DDM Single-mode	1,250
20	MP-QSFP28-SR4	Maipu MP-QSFP28-SR4 ; 100G QSFP28 100m MPO DDM Multi-mode	850

21	MP-QSFP28-LR4	Maipu MP-QSFP28-LR4 ; 100G QSFP28 10km LC DDM Single-mode	1,225
22	SFP-STACK-15	Maipu SFP-STACK-15 ; SFP+ DAC yığınlama kablosu, SFP+ to SFP+,10Gbps, 1.5 metre uzunluğunda, DAC Kablo	100
23	QSFP-STACK-10	Maipu QSFP-STACK-10 ; QSFP DAC yığınlama kablosu, QSFP to QSFP, 40Gbps, 1 metre uzunluğunda, DAC Kablo	263
24	QSFP28-STACK-30	Maipu QSFP28-STACK-30 ; QSFP28 DAC yığınlama kablosu, QSFP28 to QSFP28, 100Gbps, 3 Metre uzunluğunda, DAC Kablo	488
25	Maxtrix View	Maipu Maxtrix View ; SNMP Platform, Maipu entegre ağ yö netim sistemi, kablolu ve kablesiz entegre temel ağ yö netimi, kablolu ağ yönetimi işlevini içeren, Yönlendirici ve Anahtar Yönetimini destekler.	6,250
26	MMC-L-50	Maipu MMC-L-50 ; Yönlendirici, Anahtar ve AP dahil olmak üzere 50 düğüm cihaz lisansını yöneten cihaz yö netimi miktar lisansı	1,250
27	WA2600-823-PE	V2 Version: ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, Dual frequency, dual mode, forwarding performance of the whole device 3Gbps, 2*2:2 MIMO,inbuilt antennas, PoE power supply mode, 2*1000M RJ45 interface ; (installation accessory included)	292
28	WA2600-830-PTE	V11 Version: ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, triple frequency, dual mode, forwarding performance of the whole device 5.4Gbps, 3*2:2 MIMO,inbuilt antennas, PoE power supply mode, 1*1000M RJ45 interface and 1*2.5G RJ45 interface; (installation accessory included)	500
29	WA2600-830-PTE	V2 Version: ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, triple frequency, dual mode, forwarding performance of the whole device 5.4Gbps, 3*2:2 MIMO,inbuilt antennas, PoE power supply mode, 1*1000M RJ45 interface and 1*2.5G RJ45 interface; (installation accessory included)	512
30	WA2600-726-PTE	M1 Version:WA2600-726-PTE, Outdoor pole mount Wi-Fi6 802.11a/b/g/n/ac/ax, Dual frequency, dual mode, forwarding performance of the whole device 1.8Gbps, 2:2 MIMO, inbuilt directional antennas, 1*1000M Combo(RJ45+SFP) interface and 1*1000M RJ45 interface	512
31	WNC6600-200-AC	V2 Version: WNC6600-200-AC access controller, support 64*APs by default, max 448 APs. 12*10/100/1000M RJ45 ports and 8*10/25G SFP28 ports. Dual power supply slots.	3,423
32	WNC6600-500-AC	V2 Version: WNC6600-500-AC access controller, support 64*APs by default, max 832 APs. 12*10/100/1000M RJ45 ports and 8*10/25G SFP28 ports. Dual power supply slots.	5,829
33	NSS3330-30TXF	V1 Version: 24*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, Fixed Dual AC Power Supply	1,374
34	NSS3330-54TXF	V1 Version: 48*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, Fixed Dual AC Power Supply	1,626
35	NSS3330-30TXP	S1 Version: 24*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, 380W PoE&PoE+, Fixed One AC Power Supply	1,997