

Maipu VC350 IPPBX Datasheet

Overview

The VC350 IPPBX is a next-generation, high-capacity unified communication system developed by Maipu based on the latest upgraded technology. This 1U rack-mounted device provides four user board interfaces, supporting FXS, FXO, and E1/T1 voice interfaces. It integrates a rich set of business features, including voice, fax, conferencing, recording, etc.

The VC350 supports up to 500 registered extensions and 120 concurrent calls, facilitating remote office operations through extensions or interconnection with other IPPBX or traditional PBX systems to meet diverse user needs. Additionally, the VC350 supports various encryption and security strategies to better ensure communication security.

The VC350 is widely applicable to small and medium-sized call centers and enterprise branch offices, improving communication efficiency and reducing communication costs. It is also suitable for single-site office communication in large and medium-sized enterprises, meeting the needs of multi-point telephony networking for large corporate groups and government agencies, helping businesses and industry customers establish convenient and efficient IP telephony systems.



Features

- Provides four slots for voice module, capable of mixing FXS, FXO, and E1/T1 user boards.
- Supports up to 500 registered users and 120 concurrent calls.
- Flexible and efficient routing strategies, based on various criteria such as time and number prefix.
- Supports multi-level IVR voice menus, helping enterprises build personalized voice navigation systems.
- Can connect to traditional PSTN networks and IP voice networks.
- Flexible dialing plans with routing strategies based on time, number, source, IP, and more.
- Supports ring groups, paging groups, call queues, and conferencing.
- Supports voicemail and voice recording.

Technical Specifications

Product Model	VC350	
Hardware specification		
MCU Slot	1	
MCU Module	2*100/1000M RJ45 1* USB 2.0 1* Console	
Voice Card Slots	4	
Voice Module	8*FXS Module 8*FXO Module 4*E1/T1 Module	
Power Consumption	≤50W	
Dimension(W*D*H)mm	437*345*49 mm	
Weight	5.7kg	
Input Voltage	AC:100V ~ 240V/50Hz ~ 60Hz	
Temperature	Work Temperature: 0℃ to 45℃ Storage Temperature: -20℃ to 80℃	
Humidity	Work Humidity:10%~90%, non-condensing Storage Humidity:5%~95%, non-condensing	
Performance parameters		
Max. Registered Users	500	
Max. Concurrent Calls	120	
Max. SIP Trunk	32	
Max. E1/T1 Ports	4	
Max. FXS/FXO Ports	32	
Software Specification		
Voice Features	Protocols	SIP over UDP/TCP/TLS, SDP, RTP/RTCP/SRTP/ZRTP
	Voice Codecs	G.711a/u law, G.723.1, G.729, G.722, G.726, OPUS
	Video Codecs	VP8/H.261/H.264/H.263
	E1/T1 Signal	ISDN PRI, SS7
	Features	Voice Interruption Protection, Silence Suppression, Comfort Noise Generation (CNG), Voice Activity Detection (VAD), Echo Cancellation (G.168), max 128ms, Adaptive Jitter Buffer, Call Progress Tones: Dial Tone, Ring Back Tone, Busy Tone, NAT Traversal: STUN/DDNS, DTMF Modes: RFC2833/Signal/Inband
PBX Features	Call Management	Call Forwarding (Unconditional/No Answer/Busy), Call Waiting/Hold, Call Transfer, Call Pickup, Do Not Disturb, Three-Way Conferencing
	Group Features	Ring Group, Paging Group, Call Queue, Phone PNP
	Routing	Route Group, Custom Multi-language IVR, SMS Routing, Conferencing, Caller/Callee Number Modification, Time-Based Routing, Caller/Callee-Based Routing, Source-Based Routing, Dialing Rules, Failover Routing

	Auto Attendant	Auto Attendant
	Storage	Local CDR Storage
Network Features	Security	Fai2ban
	Routing	Static Routing, Dynamic DNS
	Diagnostics	Network Diagnostics, Custom Hosts
Management and Maintenance	Configuration	Web Management Configuration Interface, Command Line Management Configuration, Configuration Backup/Restore, Multi-language Support
	Upgrade	Firmware Upgrade: HTTP/TFTP/FTP, Auto Provision Upgrade
	Records	Call Detail Records Query and Export, System Log Query and Export
	Tools	Network Tools: Ping, Traceroute, and Nslookup, Traffic Statistics: TCP, UDP, RTP, Network Capture
FXS/FXO Voice Card		
Voice Ports	Supports 8*FXS, 8*FXO	
Interface Type	FXS/FXO Interface Type: RJ45	
Detection	Off-hook/On-hook Detection: Off-hook, On-hook, Busy Tone Polarity Reversal Flash Hook Detection	
FXO Features	Caller ID: Bellcore Type 1&2, ETSI, BT, NNT, and DTMF	
FXO Features	FXO Features: Interface Type: RJ45, Caller ID Detection: FSK, DTMF Polarity Detection, Delayed Answer Off-hook Busy Tone Detection, No Current Off-hook Detection	
E1/T1 Voice Card		
Connection	Supports E1/T1 Line Connection to Traditional PSTN Network	
E1/T1 Features	ISDN PRI, 23B+D (T1), 30B+D (E1), NT or TE Configurable, ITU-T Q.921, ITU-T Q.931	
SS7 Signaling	ITU-T, ANSI, ITU-CHINA, MTP1/MTP2/MTP3, TUP/ISUP	
Frame Format Types	E1 Frame Format Types: DF, CRC-4, CRC_ITU, T1 Frame Format Types: 4-Frame Multi-frame (F4, FT), 2-Frame Multi-frame (eF12, D3/4), Extended Super-frame (F24, ESF), Remote Switch Mode (F72, SLC96)	
Line Coding Methods	E1: NRZ, CMI, AMI, HDB3; T1: NRZ, CMI, AMI, B8ZS	

Order Information

Model	Description
VC350 Series	
VC350	Maipu VC350 IPPBX, including 1*MCU Engine Slot, 4*Voice Card Slots, Dual AC Power Supply.
Voice Module	
VCM-4E1	4-Port voice E1 module
VCM-8S	8-Port FXS module
VCM-8O	8-Port FXO module
License	
VC350-L-200	License for Max. 200 SIP register users and 60 concurrent calls
VC350-L-500	License for Max. 500 SIP register users and 120 concurrent calls

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd
Maipu Mansion, No.16, Jiuxing Avenue
Hi-Tech Zone
Chengdu, Sichuan Province
P. R. China
610041
Tel: (86) 28-65544850,
Fax: (86) 28-65544948,
URL: [http:// www.maipu.com](http://www.maipu.com)
Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.