

Maipu MPS201R-G2 Series Rack Server Datasheet

Overview

Maipu MPS201R-G2 is a high-end 2U AMD dual-socket server, supporting AMD EPYC 9004 (Genoa) series processors, 24*DDR5 memory slots, supports 2*M.2 interfaces, 2*RJ45 Ethernet ports, 1*RJ45 management port, and 11*PCIe 3.0 expansion slots. It is suitable for virtualization, cloud computing, big data processing, high-performance computing, distributed storage, enterprise markets, or telecommunications business applications, and more.



Key Features

- Supports 1 or 2 AMD EPYC 9004 series processors
- Supports 24* DDR5 memory slots, with memory maximum 4800MHz
- Modular design, allowing various combinations of PCIe and hard drive options.
- Up to 11*PCIe expansions, with optional support for 2 double-width, full-height, full-length GPU cards.

Technical Specifications

Product Model	MPS201RD08R-NV-G2	MPS201RD08R-G2	MPS201RD12R-NV-G2
Form Factor	2U 8*U.2 Direct-Connect Server	2U 08*SATA/SAS Direct-Connect Server	2U 12*U.2 Direct-Connect Server
External Hard Drive	Front: support 8*hot-swappable 3.5/2.5-inch SAS/SATA/U.2 hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules	Front: support 8*hot-swappable 3.5/2.5-inch SAS/SATA hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules	Front: support 12*hot-swappable 3.5/2.5-inch SAS/SATA/U.2 hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules
Product Model	MPS201RD12RE-G2	MPS201RD12R-G2	MPS201RD25RE-G2
Form Factor	2U 12*SATA/SAS Expansion Server	2U 12*SATA/SAS Direct-Connect Server	2U 25*SATA/SAS Expansion Server
External Hard Drive	Front: support 12*hot-swappable 3.5/2.5-inch SAS/SATA hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules	Front: support 12*hot-swappable 3.5/2.5-inch SAS/SATA hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules	Front: support 25*hot-swappable 2.5-inch SAS/SATA hard drives Rear: optional support 2*2×2.5-inch SAS/SATA or U.2 hard drive modules
System Size	748*433*87.6mm (Depth*Width*Height)		
Processor	Supports 1 or 2 AMD EPYC 9004 series (Genoa) processors		
Memory	24*DDR5 memory slots, supporting DDR5 RDIMM 4400/4800MHz memory		
Internal Storage Interface	3*Mini SAS HD interfaces, 4*SATA interfaces (2 of them support SATA DOM), 2*NVMe M.2 interfaces (size 2280)		
External Ports & Buttons	Front: 1*VGA, 2*USB3.0, Rear: 1*VGA, 2*RJ45 Gigabit Ethernet ports, 1*RJ45 Gigabit Management port, 1*COM port, 2*USB3.0		
PCIe Expansion	6*full-height PCIe slots, 4*half-height PCIe slots, 1*OCP 3.0 slots Riser1/2: 1* PCIe x 16 or 1* PCIe x 16, 2* PCIe x 8 or 2* PCIe x16 Riser3: 2* PCIe x 8 or 1* PCIe x16 Riser4: 1* PCIe x 16 or 2* PCIe x8 OCP: 1*OCP 3.0		
Security	Support TPM Module (Optional)		
Power Supply	Optional AC 220V 550W, 800W, 1300W, 1600W, 2000W, 2200W 1+1 redundant power supply(adapted to actual power requirements)		
FAN	Standard 4 hot-swappable N+1 redundant fans, supporting 8038/8056 specifications		
IPMI	IPMI 2.0		
Management	1*DC0 RJ45 Management Port		
Temperature	Working Temperature 5°C–35°C Short-term storage (≤72 hours): -40°C ~ 70°C Long-term storage (>72 hours): 20°C ~ 28°C		
Humidity	Working Humidity 20%–80%RH non-condensing Short-term storage (≤72 hours): 20% ~ 90% RH (non-condensing, including packaging) Long-term storage (>72 hours): 30% ~ 70% RH (non-condensing, including packaging)		

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd
No.16, Jiuxing avenue
Hi-Tech Zone
Chengdu, Sichuan Province
P. R. China
610041
Tel: (86) 28-65544850,
Fax: (86) 28-65544948,
URL: [http:// www.maipu.com](http://www.maipu.com)
Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.