

No	Model	Description	Price USD
1	NSS5950-32QFP	32-Port 100G QSFP28 interfaces, 6 Fan Slot, Dual Power Slots. (including telescopic rails)	15,625
2	NSS5830-56XQFP	48-Port 10G SFP+ interfaces, 8-Port 100G QSFP28 interfaces, 5 Fan Slots, Dual Power Slots	8,750
3	NSS5830-32XQFP	24-Port 10G SFP+ interfaces, 8-Port 100G QSFP28 interfaces, 5 Fan Slots, Dual Power Slots	8,125
4	WA2600-726-PTE	ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, triple frequency, dual mode, forwarding performance of the whole device 5.4Gbps, 3*2:2 MIMO,inbuilt antennas, PoE power supply mode, 1*1000M RJ45 interface and 1*2.5G RJ45 interface; (installation accessory included)	760
5	NSS5810-26XF	24-Port 10G SFP+ interfaces, 2-Port 40G QSFP+ interfaces, Dual Fan Slots, Dual Power Slots	3,000
6	NSS4330-60GXF	48*1000M SFP interfaces, 4*10G SFP+ interfaces, Dual Extension Slots, Dual Power Slots.	2,188
7	S3330-28GXF-AC	24-Port 1000M SFP fiber interfaces, 4-Port 10G SFP+ interfaces, Dual AC Power	788
8	S3230-28TXP-AC	Maipu S3230-28TXP-AC ; 24*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, POE/POE+ 380W, AC sabit güç kaynağı, ANAHTARLAMA CİHAZI	788
9	S4230-36GTXF-AC	24-Port 1000M SFP interfaces, 8-Port 100/1000M electric interfaces, 4-Port 10G SFP+ interfaces, Dual AC Power	1,770
10	S3230-54TXP-AC	Maipu S3230-54TXP-AC ; 48*10/100/1000M RJ45 port, 4*10G SFP+ fiber port, POE/POE+ 760W, AC sabit güç kaynağı, ANAHTARLAMA CİHAZI	1,438
11	S3330-28TXP-AC	24-Port 10/100/1000M electric interfaces, 4-Port 10G SFP+ interfaces, 380W PoE&PoE+, Dual AC Power	1,125
12	S3330-54TXP-AC	48-Port 10/100/1000M electric interfaces, 4-Port 10G SFP+ interfaces, 380/760W PoE&PoE+, One Extension Slots, Dual Power Slots	1,813
13	IS230-28TP-AC	24-Port 100/1000M electric interfaces, 4-Port 1G SFP interfaces, 380W PoE&PoE+, Single AC Power	438
14	IS230-54TXP-AC	48-Port 100/1000M electric interfaces, 4-Port 1/10G SFP+ interfaces, 380W PoE&PoE+, Single AC Power	1,032
15	MP-S85123-3CDLM	1.25G SFP 850nm 550m LC DDM Multi-mode	150
16	MP-S31121-3CDL20	1.25G SFP 1310nm 10-20Km LC DDM Single-mode	157
17	MP-S851X3-NCLM	10G SFP+ 850nm 300m LC DDM Multi-mode	313
18	MP-S311X2-NCL10	10G SFP+ 1310nm 10Km LC DDM Single-mode	388
19	MP-QSFP-SR4	40G QSFP+ 100m MPO DDM Multi-mode	375
20	MP-QSFP-LR4	40G QSFP+ 10km LC DDM Single-mode	1,250
21	MP-QSFP28-SR4	100G QSFP28 100m MPO DDM Multi-mode	850
22	MP-QSFP28-LR4	100G QSFP28 10km LC DDM Single-mode	1,225
23	SFP-STACK-15	SFP+ DAC stacking cable, SFP+ to SFP+,10Gbps, 1.5 meters length	100
24	WA2600-823-PE	ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, Dual frequency, dual mode, forwarding performance of the whole device 3Gbps, 2*2:2 MIMO,inbuilt antennas, PoE power supply mode, 2*1000M RJ45 interface ; (installation accessory included)	358
25	QSFP-STACK-10	QSFP DAC stacking cable, QSFP to QSFP, 40Gbps, 1.0 meters length	263
26	QSFP28-STACK-30	QSFP28 DAC stacking cable, QSFP28 to QSFP28, 100Gbps, 3 meters length	488

27	Maxtrix View	Maipu integrated network management system, wired and wireless integrated basic network management, containing the wired network management function, support Router and Switch Management.(Note: Only Software, Not include the hardware server)	6,250
28	MMC-L-50	Device management quantity license, managing 50 nodes device licenses, including Router, Switch, Firewall and AP (Note: One node license support 2 Aps)	1,250
29	IGW500-1000	IGW500-1000 internet gateway, integrated Routing, Switching, Security, Access Controller, Authentication in one box, 8*1000M Base-T+2*1000M SFP interfaces. (Controller Mode: 256 Units AP; Gateway Mode: 96 Units AP)	800
30	WA2600-830-PTE	ceiling mount Wi-Fi6 802.11a/b/g/n/ac/ax, triple frequency, dual mode, forwarding performance of the whole device 5.4Gbps, 3*2:2 MIMO,inbuilt antennas, PoE power supply mode, 1*1000M RJ45 interface and 1*2.5G RJ45 interface; (installation accessory included)	460
31	WNC6600-200-AC	V2 Version: WNC6600-200-AC access controller, support 64*APs by default, max 448 APs. 12*10/100/1000M RJ45 ports and 8*10/25G SFP28 ports. Dual power supply slots.	3,423
32	WNC6600-500-AC	V2 Version: WNC6600-500-AC access controller, support 64*APs by default, max 832 APs. 12*10/100/1000M RJ45 ports and 8*10/25G SFP28 ports. Dual power supply slots.	5,829
33	NSS3330-30TXF	V1 Version: 24*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, Fixed Dual AC Power Supply	1,374
34	NSS3330-54TXF	V1 Version: 48*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, Fixed Dual AC Power Supply	1,626
35	NSS3330-30TXP	S1 Version: 24*10/100/1000M Base-T interfaces, 6*10G SFP+ interfaces, 380W PoE&PoE+, Fixed One AC Power Supply	1,997