S4530 Series 2.5GE mGig L3 Aggregation Switch Datasheet



Overview

The S4530 series switch is a high-performance stackable 2.5GE mGig L3 aggregation routing switch developed by Maipu. It is applied in enterprise campus network and easy to deploy Layer3 switching solution that offers enhanced security, 100M/1000M/2.5GE mGig downlink and 10GE/25GE uplinks, RIP/OSPF/BGP/IS-IS, L2&L3 Multicast and SNMP management.

The S4530 series switch can be used as L3 access devices on large-sized campus networks. They can also be used as aggregation devices on small campus networks. The switches help build highly reliable enterprise campus networks that are easy to expand and manage.

The S4530 series switch includes five models, S4530-40MGF, S4530-40MGT, S4530-40MGTP, S4530-52MGT, S4530-52MGTP.

Model Name	Specification
 **S4530-40MGF**	● 24*1G/2.5G SFP + 8*100M/1000M/2.5G Base-T ● 8*10G SFP+ ● *The last 4*10G ports can be configured as 2*25G ports ● One Expansion Card ● Dual Modular Power Slots ● Dual Modular FAN Slots ● RJ45 Console/RJ45 Management/USB2.0 Port ● Switching Capacity: 480Gbps
 **S4530-40MGT**	● 24*100M/1000M/2.5G Base-T + 8*1G/2.5G SFP ● 8*10G SFP+ ● *The last 4*10G ports can be configured as 2*25G ports ● One Expansion Card ● Dual Modular Power Slots ● Dual Modular FAN Slots ● RJ45 Console/RJ45 Management/USB2.0 Port ● Switching Capacity: 480Gbps
 **S4530-40MGTP**	● 24*100M/1000M/2.5G Base-T + 8*1G/2.5G SFP ● 8*10G SFP+ ● *The last 4*10G ports can be configured as 2*25G ports ● Max. 1480W 802.3bt PoE++; Max. 90W/Port ● One Expansion Card ● Dual Modular Power Slots ● Dual Modular FAN Slots ● RJ45 Console/RJ45 Management/USB2.0 Port ● Switching Capacity: 480Gbps

 **S4530-52MGT**	● 48*100M/1000M/2.5G Base-T ● 4*1/10G SFP+ ● *The last 4*10G ports can be configured as 2*25G ports ● One Expansion Card ● Dual Modular Power Slots ● Dual Modular FAN Slots ● RJ45 Console/RJ45 Management/USB2.0 Port ● Switching Capacity: 480Gbps
 **S4530-52MGTP**	● 48*100M/1000M/2.5G Base-T + 4*1/10G SFP+ ● 4*1/10G SFP+ ● *The last 4*10G ports can be configured as 2*25G ports ● One Expansion Card ● Max. 1480W 802.3bt PoE++; Max. 90W/Port ● Dual Modular Power Slots ● Dual Modular FAN Slots ● RJ45 Console/RJ45 Management/USB2.0 Port ● Switching Capacity: 480Gbps

*Note: After configuring 25G work mode, reboot the device to apply the change.

Key Features

- **100M/1000M/2.5GE mGig Interfaces**

With the rise of Wi-Fi 7, the limitations of traditional gigabit switch ports are becoming increasingly evident. To meet the growing demand for higher bandwidth in next-generation wireless and wired networks, 2.5GE switches are poised to become the mainstream in the future. The S4530 series switch is designed for such kind of scenarios, it provides 100M/1000M/2.5GE RJ45 interfaces, 1G/2.5G SFP interfaces and 1/10/25G SFP28 or 40G QSFP+ uplinks.

- **Intelligent Stacking Technology**

The S4530 series switch is equipped with Maipu VST stacking function. VST (Virtual Switching Technology) stacking combines multiple switches to form a logical virtual switch via 10G SFP+ or 40G QSFP+ ports, improving device and link reliability, network expansion, and simplifying configuration and management.

- **Zero Touch Provisioning**

The S4530 series switch features advanced Zero Touch Provisioning (ZTP) capabilities, streamlining the deployment process for network administrators. With ZTP, the switch can automatically discover and load necessary version files from a file server via a DHCP server or a USB flash disk, eliminating the need for manual intervention during initial setup. This automation reduces configuration errors, accelerates the deployment process, and enhances overall network efficiency, making the S4530 series switch an ideal choice for scalable and dynamic network environments.

- **High Availability**

The S4530 series switch offers advanced redundancy and reliability features, catering to diverse networking requirements. In addition to supporting traditional spanning tree protocols such as STP, RSTP, and MSTP, the switch also complies with the ITU-T G.8032 international standard. This Ethernet Ring Protection Switching (ERPS) protocol enables rapid 50ms failover within Ethernet ring network topologies, ensuring seamless connectivity and minimal downtime.

- **Perfect Security Policy**

The S4530 series switch offers a comprehensive suite of security features, including user authentication, port security, ACLs, loopback detection, and 802.1X authentication. It also incorporates IP Source Guard, DHCP/ND Snooping, Host Guard, Dynamic ARP Inspection. These robust security functions ensure user access and network protection. Additionally, the switch supports MAC+IP+VLAN binding, 802.1X authentication, and countermeasures against network storm, DOS/DDOS, ARP, and protocol packet attacks. This makes the S4530 series ideal for large-scale, multi-service, and complex-traffic networks.

- **Advanced QoS**

The S4530 series switch offers sophisticated QoS capabilities for optimal network performance. Supporting eight queues per port and advanced scheduling algorithms such as SP, RR, WRR, and WDRR, the switch effectively manages traffic prioritization and resource allocation.

The switch accommodates diverse priority mapping techniques, including 802.1p, CoS, and DSCP, enabling fine-grained control over traffic classification and prioritization. With granular port traffic rate limiting and time-based controls, network administrators can regulate bandwidth usage as needed.

To optimize network performance and minimize congestion, the S4530 series switch employs advanced congestion management techniques, such as Tail Drop and RED packet loss algorithms. These mechanisms help maintain seamless network operation while ensuring efficient delivery of critical data.

- **IPv4&IPv6 Dual-stack Ability**

The S4530 series switch is built on an IPv4/IPv6 dual-stack platform, delivering hardware-based, wire-speed forwarding for both IPv4 and IPv6 traffic. The switch supports IPv4/IPv6 Layer 3 routing protocols, including

RIPng, OSPFv3, BGP4+, and IS-IS for IPv6. These IPv6 capabilities enable seamless deployment on pure IPv4, pure IPv6, or dual-stack networks, facilitating a smooth transition from IPv4 to IPv6 infrastructure.

- **Rich Network Management**

The S4530 series switch offers a comprehensive set of management options. These options encompass network management protocols like SNMP and TR-069, configuration and control options like Netconf/Yang and CLI, monitoring and diagnostic tools such as SYSLOG. These versatile features enable network administrators to effectively manage, monitor, and maintain optimal network performance both locally and via the cloud.

- **Free Licensing Policy**

Maipu consistently adheres to a "One-time investment" free license policy, ensuring that standard and advanced features are not differentiated across versions. This approach guarantees that customers receive new firmware updates without incurring additional charges. In comparison to other manufacturers, Maipu's free license policy safeguards both short-term and long-term user investments, providing an unparalleled value proposition.

Technical Specifications

Product Model	S4530-40MGF	S4530-40MGT	S4530-40MGTP	S4530-52MGT	S4530-52MGTP
Hardware Specification					
Hardware Version	V1	V1	V1	V1	V1
Physical Service Port	8*100M/1000M/2.5GE Base-T interfaces 24*1G/2.5G SFP interfaces 8*10G SFP+ interfaces	24*100M/1000M/2.5GE Base-T interfaces 8*1G/2.5G SFP interfaces 8*10G SFP+ interfaces		48*100M/1000M/2.5GE Base-T interfaces 4*10G SFP+ interfaces	
Power Slot	Dual				
Fan Slot	Dual				
Expansion Card Slot	One				
PoE Standard	NA	NA	IEE 802.3af/at/bt	NA	IEE 802.3af/at/bt
Max. PoE Power Consumption	NA	NA	1480W	NA	1480W
Power Consumption (Without PoE)	≤116W	≤85W	≤85W	≤79W	≤85W
Dimension(W*D*H) mm	442*380*44.2mm				
Physical Management Port	1*RJ45 Console Port 1*DC0 Port 1*USB2.0 Port				
Input Voltage	AC :100-240V/50-60Hz				
Temperature	Work Temperature : 0℃ to 45℃ Storage Temperature : -40℃ to 70℃				
Humidity	Work Humidity:10%～90%, non-condensing Storage Humidity:5%～95%, non-condensing				
Anti-Lightning	6KV				
Anti-Static	6KV				
MTBF	>100000 hours				
Performance Parameters					
Switching Capacity	480Gbps				
Forwarding Performance(64-byte)	357Mpps				
CPU	2-Core, 1.0GHz				
Flash	8GB				
RAM	2GB				
Max MAC Address Entry	65K/114K				
Jumbo Frame	12K				
ARP Entry	32K				

Max ND Entry	32K
VLAN Entry	4K
LACP Group	128
LACP Member in Group	8
MSTP Instance	64
Max IPv4 Routing Entry	32K
Max IPv6 Routing Entry	16K
L2 Multicast Entry	8K
L3 Multicast Entry	8K
VRF Entry	1K
VRRP Group	255

Software Specification		
Interface	Physical Interface	Auto MDI/MDIX, Port Type UNI/NNI, Port Speed, Port MTU, Switch Port, Routed Port, Port Loopback, Port Energy Control
	Logic Interface	Loopback Interface, Tunnel Interface, Null Interface, L2/L3 VLAN Interface, L3 Ethernet Interface
	MAC Address Management	Storm Control, Flood Control, MAC Address Aging Time, Mac Address Learning on|off, Mac Address Learning Limitation, Mac Address VLAN Bunding, MAC Debug, MAC Flapping, MAC Blackhole
VLAN	VLAN Management	VLAN, VLAN PVID, VLAN Tag/Untag, VLAN Trunk, MAC VLAN, Protocol VLAN, Subnet VLAN, Voice VLAN, Guest VLAN, VLAN Debug, VLAN Isolation
Ring Protection	Spanning Tree Protocols	STP/RSTP/MSTP, BPDU Guard, Flap Guard, Loop Guard, Root Guard, TC Guard, Edge Port
	Other Ring Protocols	VIST/VIST+, G.8032(ERPSv1&v2)
Link Aggregation	LACP Configuration	Static LACP, Dynamic LACP, LACP Port Priority, LACP Load Balance, LACP Rate Failover, LACP Debug
Error Handling	Error-disable Configuration	Error-disable Based on bpduguard|DAI|DHCP Snooping|Link-Flap|Loopback-detect|Port Security|Storm Control|Transceiver Power, Error-disable Recovery
Fault Detection	Fault Detection Features	Track, Loop-back Detection, CFM (802.1ag), EFM (802.3ah)
IP Services	IP Protocol	ARP, ND, IPv6 Auto-Config, DNS, ICMPv4/v6
	Routing Protocol	Static Routing v4/v6, RIP/RIPng, OSPF v2/v3, BGP/BGP+, ISIS/ISIS v6, VRRP/VRRP v3, PBR v4/v6, ECMP, IRMP, VRF
	DHCP Service	DHCP v4/v6 Server, DHCP v4/v6 Client, DHCP v4/v6 Relay, DHCP v4/v6 Snooping, DHCP Option 82, DHCPv6 Option 18/37
Multicast Protocols	L2 Multicast Protocols	IGMPv1/v2/v3 Snooping, IGMP Snooping Proxy, MLD Snooping
	L3 Multicast Protocols	IGMPv1/v2/v3, MLD, PIM-SM, PIM-SSM, PIM-DM, PIM-SDM, MSDPv4
QoS	Priority Mapping	802.1P Priority, DSCP priority
	Traffic Classification	Three Color Marker, Priority Remark, Traffic Redirect, Traffic Meter, Traffic Mirror
	Traffic Control	Rate Limit, Traffic Shaping
	Scheduling Algorithm	SP, RR, WRR, WDRR, SP+WRR, SP+WDRR
	Congestion Management	Tail-drop, RED, WRED
Security	Port Security	Port Security On aging|deny|permit|violation|ACL, Sticky MAC

	Network Access Control	IPv4/v6 Source Guard (ISG), DHCPv4/v6 Snooping, ND Snooping, ARP Snooping, Host Guard, MAC Authentication
	Threat Prevention	Dynamic ARP Inspection (DAI), ARP Check, ARP Speed Limit, ARP Source Suppression
	Access Control List	Standard IP ACL, Extended IP ACL, Standard MAC ACL, Extended MAC ACL, Standard Hybrid ACL, Extended Hybrid ACL, Standard IPv6 ACL, Extended IPv6 ACL, Time-based ACL
	Anti-Attack	Anti-Attack Detect|Drop|Flood|Log, URPF, CPU Protection, White List, Black List
	AAA	AAA, Radius, TACACS+, 802.1x, Portal
High Availability	Device Virtualization	VST, M-LAG
	Multi-Active Detection	MAD LACP, MAD BFD, MAD Fast-Hello
	High Availability Protocols	UDLD, MTLK, ULPP, EEP, VRRP, VRRPv3
	BFD	BFD for Static Routev4|RIP|OSPF|BGP|ISIS BFD for Static Routev6|RIPng|OSPFv3|BGP4+|ISISv6 LACP BFD, BFD for VRRP/VRRPv3, BFD for PIMv4-SM
Configuration and Maintenance	Monitoring and Diagnostics	SPAN, sFlow, Telemetry, LLDP, IP-SLA, BSM, Keepalive Gateway
	Device Management	TR069, SNMP v1/v2/v3, MIB, SYSLOG, WEB(HTTP/HTTPS), RBAC, CLI, Telnet, SSHv1/v2, FTP/SFTP/TFTP, SCP, NTP Server/Client, Debug, ISSU, Hot Patch, Configuration Rollback, Cloud Management
	Zero Touch Provisioning	ZTP Provisioning Through DHCP Server, ZTP Provisioning Through USB Flash Disk
Network Virtualization	Software Defined Networking (SDN)	Netconf, RESTConf, Ansible
IEEE Standard	IEEE 802.3 (10BASE-T) IEEE 802.3u (100BASE-T) IEEE 802.3z (1000BASE-X) IEEE 802.3ab (1000BASE-T) IEEE 802.3bz (2500BASE-T) IEEE 802.3ae (10GBASE-X) IEEE 802.3by (25GBASE-X) IEEE 802.3ba (40GBASE-X) IEEE 802.3ah (Ethernet in the First Mile Operations, Administration, and Maintenance) IEEE 802.1x (Port-Based Network Access Control) IEEE 802.3ad (Link Aggregation) IEEE 802.3x (Flow Control) IEEE 802.3af/at/bt (PoE/PoE+/PoE++) IEEE 802.3az (Energy Efficient Ethernet) IEEE 802.1d (Spanning Tree Protocol) IEEE 802.1ab (Link Layer Discovery Protocol) IEEE 802.1Q (Virtual LAN) IEEE 802.1w (Rapid Spanning Tree Protocol) IEEE 802.1s (Multiple Spanning Tree Protocol) IEEE 802.1p (Class of Service Priority) IEEE 802.1ag (Connectivity Fault Management)	

Order Information

Model	Description
S4530 Series Host	
S4530-40MGF	V1 Version: 8*100M/1000M/2.5GE Base-T interfaces, 24*1/2.5G SFP interfaces, 8*1/10G SFP+ interfaces, One Extension Slot, Dual FAN Slots, Dual Power Slots. Note: The last 4*10G ports can be configured as 2*25G ports.
S4530-40MGT	V1 Version: 24*100M/1000M/2.5GE Base-T interfaces, 8*1/2.5G SFP interfaces, 8*1/10G SFP+ interfaces, One Extension Slot, Dual FAN Slots, Dual Power Slots. Note: The last 4*10G ports can be configured as 2*25G ports.
S4530-40MGTP	V1 Version: 24*100M/1000M/2.5GE Base-T interfaces, 8*1/2.5G SFP interfaces, 8*1/10G SFP+ interfaces, One Extension Slot, Dual FAN Slots, Dual Power Slots, PoE/PoE+/PoE++ Enable. Note: The last 4*10G ports can be configured as 2*25G ports.
S4530-52MGT	V1 Version: 48*100M/1000M/2.5GE Base-T interfaces, 4*1/10G SFP+ interfaces, One Extension Slot, Dual FAN Slots, Dual Power Slots. Note: The last 4*10G ports can be configured as 2*25G ports.
S4530-52MGTP	V1 Version: 48*100M/1000M/2.5GE Base-T interfaces, 4*1/10G SFP+ interfaces, One Extension Slot, Dual FAN Slots, Dual Power Slots, PoE/PoE+/PoE++ Enable. Note: The last 4*10G ports can be configured as 2*25G ports.
Power Module	
AD150M-HS0N	V1 Version: 150W AC Power Supply Module for Non-POE Model
AD250-1S005E-B	V1 Version: 250W AC Power Supply Module for S4530-40MGF
AD530M-HD1B	V1 Version: 530W AC Power Supply Module for POE Model
AD910M-HD1B	V1 Version: 910W AC Power Supply Module for POE Model
FAN Module	
FAN-01F-01B	V2 Version: FAN-01F-01B FAN Module
Extension Module	
SM4C-8XGEF	V1 Version: 8-Port 10G SFP+ interfaces Extension Module
SM4C-4XGEF	V1 Version: 4-Port 10G SFP+ interfaces Extension Module
SM4C-2QXGEF	V1 Version: 2-Port 40G QSFP+ interfaces Extension Module

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

Maipu Communication Technology Co., Ltd
Maipu Mansion, No.16, Jiuxing Avenue
Hi-Tech Zone
Chengdu, Sichuan Province
P. R. China
610041
Tel: (86) 28-65544850,
Fax: (86) 28-65544948,
URL: http:// www.maipu.com
Email: overseas@maipu.com

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.